

Amendment Dated: January 23, 2006

IN THE CLAIMS:

Please amend claims 1-10 as follows:

1. (Currently Amended) A portable videodisc player ~~for videodisc~~ with a ~~an~~ upwardly and axially rotatable screen, comprising: which can rotate in upturn and/or turn around, including a main body comprising a disc driver means and a disc information read/processing means and a display cover board with a display screen; an upturn hinge means is ~~set~~ disposed at a side edge of the main body and a side edge of the display cover board; a cable connects ~~between~~ the main body and the display cover board;

~~Wherein~~ wherein the main body of the upturn hinge means is T-shaped cannula, ~~the~~ a horizontal end of the cannula is fixed on the side of the display cover board and is a shaft having a damper; ~~the~~ a vertical end is used as a rotation shaft which is mounted on the main body; a cable ~~aecross~~ passes through ~~the~~ an inner hole of the main body of the upturn hinge means to ~~make~~ connect the main body of the player and the display cover board ~~eenected~~; the display cover board ~~can rotate~~ is rotatable within 180 degrees relatives to the respective vertical axes ~~and the horizontal axes of its main body, respectively.~~

2. (Currently Amended) The portable videodisc player ~~for videodisc~~ with a ~~screen which can rotate in upturn and/or turn around of claim 1, wherein there is a~~ further including recess in the centre ~~a center of the~~ a rear end of the display cover board; the

Amendment Dated: January 23, 2006

horizontal end of the body of the upturn hinge means is disposed in the recess, ~~a~~an end of the horizontal end of the body of the upturn hinge means is a hollow pipe for installing accommodating cables, ~~it~~and extends into a side wall of the recess to enable the hinge, ~~the~~other an opposite end is ~~tightly stick~~secured to ~~the~~ another side wall of the recess and ~~the a~~ turning free end of the damper is received therein, the fixed end of the damper is secured to ~~the a~~ rear portion of the side wall of the recess; ~~the centre~~a center of the back wall of the upper surface of the main body has ~~a~~an upright hole, the vertical end of the body of the upturn hinge means is inserted into the upright hole.

3. (Currently Amended) The portable videodisc player ~~for videodisc~~ ~~with a screen which can rotate in upturn and/or turn around~~ of claim 2, wherein the damper is of a key shape, of which the shaft head has a plurality of C-shaped rub pieces with protruding ears at their periphery, ~~and these protruding~~ said ears are ~~lined~~disposed in a line forming a protruding ridge, ~~the a~~a piece-shaped tail portion of the damper has a fixed hole; there is a slot set in ~~the an~~ inside wall ~~of the end~~ of the horizontal end of the upturn hinge means for installing the damper, ~~the said~~ head ~~portion~~ having rub pieces of the damper inserts into the above end of the upturn hinge means and the protruding ridge is ~~stick~~fastened to ~~the~~ said slot; ~~a screw cross through the fixed hole in the end of the damper fixed~~ and the damper is fixed onto the back of side wall of the recess of the display cover board.

Amendment Dated: January 23, 2006

4. (Currently Amended) The portable videodisc player ~~for videodisc~~  
~~with a screen which can rotate in upturn and/or turn around of claim 1 or claim 2 or claim 3,~~  
~~wherein there is further including~~ a locating tray at ~~the~~ an interface of the vertical end and the  
horizontal end of the body of the upturn hinge means, the bottom of the locating tray lies on  
the shaft of the horizontal end, ~~there~~ in the outer side of the vertical end ~~set are~~ two recesses  
which are symmetric to the shaft line of the vertical end, ~~there are~~ two bump pearls are  
disposed in the corresponding recesses on ~~the two side~~ sides of ~~the~~ an upright hole of ~~the~~ an  
upper surface of the main body.

5. (Currently Amended) The portable videodisc player ~~for videodisc~~  
~~with a screen which can rotate in upturn and/or turn around of claim 4,~~ wherein on the outer  
circumference of the ~~fix~~ hole of the body of the upturn hinge means there is a locating  
protruding ear on the back side of the ~~axes~~ axis line of the horizontal end, ~~there is a~~ baffle  
plate is located on each side of the corresponding locating ear of the upper face of the main  
body.

6. (Currently Amended) The portable videodisc player ~~for videodisc~~  
~~with a screen which can rotate in upturn and/or turn around of claim 1 or claim 2 or claim 3,~~  
wherein there is a locating loop slot set around ~~the~~ an outer circumference of ~~the~~ a lower  
portion of the vertical end of the body of the upturn hinge means, ~~the~~ an upper side wall of

Amendment Dated: January 23, 2006

the locating loop slot is parallel to the lower end of the upright hole of the upper face of the main body, a flexible clip ~~stick~~ is fastened to the locating loop slot and ~~withstand to~~ the lower end of the said upright hole.

7. (Currently Amended) The portable videodisc player ~~for videodisc~~ ~~with a screen which can rotate in upturn and/or turn around~~ of claim 6, wherein there is a locating pole which extends downwards to limit the turning range of the ~~a~~ head of the flexible clip.

8. (Currently Amended) The portable videodisc player ~~for videodisc~~ ~~with a screen which can rotate in upturn and/or turn around~~ of claim 6, wherein there is a baffle plate below the upright hole of the upper surface of the main body, a round-arc-like recess corresponding to the above upright hole is set on the baffle plate, the recess shelters a part of the edge of vertical end hole of the body of the upturn hinge means in the upright hole, a cable crosses through the lower portion of the ~~a~~ recess mouth to the vertical end hole of the body of the upturn hinge means.

9. (Currently Amended) The portable videodisc player ~~for videodisc~~ ~~with a screen which can rotate in upturn and/or turn around~~ of claim 1 ~~or claim 2 or claim 3~~, wherein there is further including a recess in the centre ~~a center~~ of the front end of the display

Amendment Dated: January 23, 2006

cover board, a two-way lock latch is disposed within the recess; ~~there is a~~ recess hole is set in ~~the centre~~ a center of the front end of the main body, a button hook is fixed in the recess hole, the two-way lock latch and the button hook form a two-way locking means.

10. (Currently Amended) The portable videodisc player ~~for videodisc~~ ~~with a screen which can rotate in upturn and/or turn around~~ of claim 69, wherein the two-way lock latch assumes a rectangular board shape, its lower portion includes a rectangular ~~open~~opening, its upper portion includes a short shaft and a ladder shaft both ~~extend~~ extending outwards from two sides, ~~the~~ a ladder of the ladder shaft includes a pair of vertically symmetrical wedge ~~mouth~~ mouths ~~which is symmetry from up to down; there is another~~ an A-shaped locating block having a shaft hole in ~~the~~ an upper portion is sleeved on a thin shaft at ~~the~~ an outer side of the wedge mouth of the ladder shaft, ~~the~~ a waist of the locating block has a locating wedge extending to the wedge mouth of the ladder shaft, ~~the~~ an outer side of the locating block on the thin shaft of the ladder shaft has a spring; ~~the~~ button hook is a piece block whose cross section assumes an L-shape with the front end extending forwards forming a button and the rear end forming a button hook which is ~~assorted~~ engageable with ~~the open~~ an opening of the two-way lock and is formed of ~~the~~ upwards and backwards extending portions, the waist of the piece block ~~extend~~ extends from two side forming blocks, ~~the~~ a rear side extends backwards forming two guide ~~pole~~ poles, ~~there is a~~ reposition spring on each pole; the button of the button-hook extends forward via the recess of the front end of

Amendment Dated: January 23, 2006

the main body ~~extend forwards~~ is located; ~~a~~ an end of the reposition spring ~~withstand~~ engages  
the back-end face of the button-hook, another end of the reposition spring ~~withstand~~ engages  
the support wall of the rear of the front end of the recess of the main body.